

Elite Series

Digital Noise Reduction (DNR) Vandal-Resistant Color Dome Camera

EV-2615-NKEQ 2.8~11.0mm Varifocal Lens, Digital Slow Shutter

The ENFORCER EV-2615-NKEQ is the ideal solution to protect areas in poor lighting conditions. An ultra-low lux rating of 0.002 allows the camera to see in almost total darkness.

Features:

- ▶ 1/3" Sony Super HAD CCD
- ▶ 520 TV lines for high resolution
- ▶ Digital Slow Shutter (DSS) up to x128
- ▶ Automatic and manual gain control
- ▶ Mechanical IR cut filter
- ▶ CDS sensor
- ▶ On-screen display with included remote control
- ▶ Varifocal lens can cover a wide area or focus in on a specific target
- ▶ 360° triple-axis rotation
- ▶ Vandal-resistant and weatherproof
- ▶ Easy adjustment of focus and zoom
- ▶ Dual Voltage: 12VDC or 24VAC
- ▶ Service monitor port
- ▶ Ceiling and Wall Mounts available
- ▶ Programmable motion detection, backlight compensation and privacy zones



Flush or surface mountable!



Typical Camera Rated at 0.1 Lux




Actual comparison
photos. Taken 15
minutes before sunrise.

EV-2615-NKEQ Rated at 0.002 Lux



On-screen Display and Remote Control:

The on-screen display can program the camera for the poorest of lighting conditions. Using the included remote control, adjustments can be made to the gain control, digital noise reduction, and digital slow shutter to show crisp, clear images regardless of the lighting.



On-Screen Display
Main Menu



Included Remote Control

Specifications:

Image sensor	1/3" Sony Super HAD CCD
Resolution	520 TV lines color, 540 TV lines B/W
Pickup elements	768 x 494 pixels
Lens	f = 2.8 ~ 11 mm varifocal, F1.2 DC auto iris
Digital slow shutter (DSS)	OFF, ON: 2x ~ 32x
On-screen display (OSD)	Built-in
Digital noise reduction	High / Middle / Low / OFF
Sync	Internal
Shutter speed	x128 speed - 1/60 ~ 1/120,000 sec
Iris control	DC auto iris
Gain control	Auto
White balance	ATW / AWC / Manual
Video output	1 Vp-p composite output, 75 Ohms.
S/N ratio	> 50dB (AGC off)
Power source (+/-10%)	24VAC or 12VDC
Ambient temperature	14° ~ 122° F (-10° ~ 50° C)
Varifocal lens	2.8 ~ 11.0 mm
Minimum illumination	0.002 Lux
Power consumption @ 24VAC	Max. 5.5VA
Power consumption @ 12VDC	Max: 220mA
Weight	4 lbs. 6 oz. (2.0 kg)

Other Models Available:



Day Night

EV-2605-NKEQ

- ▶ True Day/Night Operation
- ▶ 1/3" Sony Super HAD
- ▶ 550 TV Lines
- ▶ Mechanical IR cut filter



Day Night

EV-2606-NJEQ

- ▶ 36 IR LEDs
- ▶ 1/3" Sony Super HAD
- ▶ 550 TV Lines
- ▶ Mechanical IR cut filter



WDR

EV-2625-NKEQ

- ▶ Wide Dynamic Range
- ▶ 1/3" Pixim DPS Image Sensor
- ▶ 540 TV Lines
- ▶ On-screen display